

Networked Programs

Chapter 12



Python for Informatics: Exploring Information
www.py4inf.com





open.michigan

Unless otherwise noted, the content of this course material is licensed under a Creative Commons Attribution 3.0 License.

<http://creativecommons.org/licenses/by/3.0/>.

Copyright 2009- Charles Severance, Jim Eng



TCP Connections / Sockets

"In computer networking, an Internet **socket** or network **socket** is an endpoint of a bidirectional **inter-process** communication flow across an **Internet** Protocol-based computer network, such as the **Internet**."




http://en.wikipedia.org/wiki/Internet_socket

TCP Port Numbers

- A port is an **application-specific** or process-specific software communications endpoint
- It allows multiple networked applications to coexist on the same server.
- There is a list of well-known TCP port numbers

http://en.wikipedia.org/wiki/TCP_and_UDP_port




Clipart: <http://www.clker.com/search/networksym/>

Common TCP Ports

- Telnet (23) - Login
- SSH (22) - Secure Login
- HTTP (80)
- HTTPS (443) - Secure
- SMTP (25) (Mail)
- IMAP (143/220/993) - Mail Retrieval
- POP (109/110) - Mail Retrieval
- DNS (53) - Domain Name
- FTP (21) - File Transfer

http://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers



Sometimes we see the port number in the URL if the web server is running on a "non-standard" port.

Sockets in Python

- Python has built-in support for TCP Sockets


```
import socket
```

```
mysock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)  
mysock.connect( ('www.py4inf.com', 80) )
```

Host




Port



<http://www.pythonlearn.com/code/socket1.py>



<http://xkcd.com/353/>




HTTP

- The HyperText Transport Protocol is the set of rules to allow browsers to retrieve web documents from servers over the Internet

What is a Protocol?

- A set of rules that all parties follow for so we can predict each other's behavior
- And not bump into each other
 - On two-way roads in USA, drive on the right hand side of the road
 - On two-way roads in the UK drive on the left hand side of the road



<http://www.flickr.com/photos/kitcowan/2103850699/>

http://en.wikipedia.org/wiki/Tin_can_telephone

Getting Data From The Server

- Each the user clicks on an anchor tag with an href= value to switch to a new page, the browser makes a connection to the web server and issues a “GET” request - to GET the content of the page at the specified URL
- The server returns the HTML document to the Browser which formats and displays the document to the user.






Browser



Web Server

80




Browser






GET <http://www.dr-chuck.com/page2.htm>



Web Server

80

GET <http://www.dr-chuck.com/page2.htm>



Browser



```
<h1>The Second Page</h1>
<p>
If you like, you can switch
back to the
<a href="page1.htm">
First Page</a>.
</p>
```

Web Server

80

GET http://www.dr-chuck.com/page2.htm

Browser


```
<h1>The Second Page</h1>
<p>
If you like, you can switch
back to the
<a href="page1.htm">
First Page</a>.
</p>
```



Lets Write a Web Browser!

“Hacking” HTTP

```
$ telnet www.dr-chuck.com 80
Trying 74.208.28.177...
Connected to www.dr-chuck.com.
Escape character is '^]'.
GET http://www.dr-chuck.com/page1.htm
<h1>The First Page</h1>
<p>
If you like, you can switch to the
<a href="http://www.dr-chuck.com/page2.htm">
Second Page</a>.
</p>
```



Port 80 is the non-encrypted HTTP port


An HTTP Request in Python

```
import socket
```

```
mysock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
mysock.connect(('www.py4inf.com', 80))
mysock.send('GET http://www.py4inf.com/code/romeo.txt HTTP/1.0\n\n')
```

```
while True:
    data = mysock.recv(512)
    if ( len(data) < 1 ) :
        break
    print data
```

```
mysock.close()
```



<http://www.pythonlearn.com/code/socket2.py>

HTTP/1.1 200 OK

Date: Sun, 14 Mar 2010 23:52:41 GMT

Server: Apache

Last-Modified: Tue, 29 Dec 2009 01:31:22 GMT

ETag: "143c1b33-a7-4b395bea"

Accept-Ranges: bytes

Content-Length: 167

Connection: close

Content-Type: text/plain

But soft what light through yonder window breaks

It is the east and Juliet is the sun

Arise fair sun and kill the envious moon

Who is already sick and pale with grief

HTTP Header

```
while True:
    data = mysock.recv(512)
    if ( len(data) < 1 ) :
        break
    print data
```

HTTP Body

<http://www.pythonlearn.com/code/socket2.py>

Making HTTP Easier With urllib

Using `urllib` in Python

- Since HTTP is so common, we have a library that does all the socket work for us and makes web pages look like a file

```
import urllib

fhand = urllib.urlopen('http://www.py4inf.com/code/romeo.txt')

for line in fhand:
    print line.strip()
```

<http://www.pythonlearn.com/code/urllib1.py>

`urllib1.py`


```
import urllib

fhand = urllib.urlopen('http://www.py4inf.com/code/romeo.txt')

for line in fhand:
    print line.strip()
```

But soft what light through yonder window breaks
It is the east and Juliet is the sun
Arise fair sun and kill the envious moon
Who is already sick and pale with grief

<http://docs.python.org/library/urllib.html>

urllib l.py

Like a file...

```
import urllib

fhand = urllib.urlopen('http://www.py4inf.com/code/romeo.txt')

counts = dict()
for line in fhand:
    words = line.split()
    for word in words:
        counts[word] = counts.get(word,0) + 1
print counts
```

urlwords.py

Reading Web Pages

```
import urllib
```

```
fhand = urllib.urlopen('http://www.dr-chuck.com/page1.htm')  
for line in fhand:  
    print line.strip()
```

```
<h1>The First Page</h1>  
<p>  
If you like, you can switch to the  
<a href="http://www.dr-chuck.com/page2.htm">  
Second Page</a>.  
</p>
```


urllib1.py

Going from one page to another...

```
import urllib
```

```
fhand = urllib.urlopen('http://www.dr-chuck.com/page1.htm')  
for line in fhand:  
    print line.strip()
```

```
<h1>The First Page</h1>  
<p>  
If you like, you can switch to the  
<a href="http://www.dr-chuck.com/page2.htm">  
Second Page</a>.  
</p>
```



```
import urllib
```

```
fhand = urllib.urlopen('http://www.dr-chuck.com/page1.htm')  
for line in fhand:  
    print line.strip()
```


Parsing HTML (a.k.a Web Scrapping)

What is Web Scraping?

- When a program or script pretends to be a browser and retrieves web pages, looks at those web pages, extracts information and then looks at more web pages.
- Search engines scrape web pages - we call this “spidering the web” or “web crawling”

http://en.wikipedia.org/wiki/Web_scraping

http://en.wikipedia.org/wiki/Web_crawler



GET

HTML

GET

Server

```
charles-severances-macbook-air:Scraping csev$ python
Python 2.5 (r25:51918, Sep 19 2006, 08:49:13)
[GCC 4.0.1 (Apple Computer, Inc. build 5341)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> import urllib
>>> f = urllib.urlopen("http://www.dr-chuck.com/")
>>> contents = f.read()
>>> f.close()
>>> print len(contents)
95328
>>> print contents[0:30]
<html>
<head>
  <title>Dr. C
>>> |
```

HTML

Why Scrape?

- Pull data - particularly social data - who links to who?
- Get your own data back out of some system that has no “export capability”
- Monitor a site for new information
- Spider the web to make a database for a search engine

Scraping Web Pages

- There is some controversy about web page scraping and some sites are a bit snippy about it.
- Google: facebook scraping block
- Republishing copyrighted information is not allowed
- Violating terms of service is not allowed


<http://www.facebook.com/terms.php>

User Conduct

You understand that except for advertising programs offered by us on the Site (e.g., Facebook Flyers, Facebook Marketplace), the Service and the Site are available for your personal, non-commercial use only. You represent, warrant and agree that no materials of any kind submitted through your account or otherwise posted, transmitted, or shared by you on or through the Service will violate or infringe upon the rights of any third party, including copyright, trademark, privacy, publicity or other personal or proprietary rights; or contain libelous, defamatory or otherwise unlawful material.

In addition, you agree not to use the Service or the Site to:

- harvest or collect email addresses or other contact information of other users from the Service or the Site by electronic or other means for the purposes of sending unsolicited emails or other unsolicited communications;
- use the Service or the Site in any unlawful manner or in any other manner that could damage, disable, overburden or impair the Site;
- use automated scripts to collect information from or otherwise interact with the Service or the Site;



The Easy Way - BeautifulSoup

- You could do string searches the hard way
- Or use the free software called BeautifulSoup from www.crummy.com

<http://www.crummy.com/software/BeautifulSoup/>

Place the BeautifulSoup.py file in the same folder as your Python code...

```
import urllib
from BeautifulSoup import *

url = raw_input('Enter - ')
html = urllib.urlopen(url).read()
soup = BeautifulSoup(html)

# Retrieve a list of the anchor tags
# Each tag is like a dictionary of HTML attributes

tags = soup('a')

for tag in tags:
    print tag.get('href', None)
```

urlinks.py

```
<h1>The First Page</h1>  
<p>  
If you like, you can switch to the  
<a href="http://www.dr-chuck.com/page2.htm">  
Second Page</a>.  
</p>
```

```
html = urllib.urlopen(url).read()  
soup = BeautifulSoup(html)  
tags = soup('a')  
for tag in tags:  
    print tag.get('href', None)
```

```
python urllinks.py  
Enter - http://www.dr-chuck.com/page1.htm  
http://www.dr-chuck.com/page2.htm
```

Summary

- The TCP/IP gives us pipes / sockets between applications
- We designed application protocols to make use of these pipes
- HyperText Transport Protocol (HTTP) is a simple yet powerful protocol
- Python has good support for sockets, HTTP, and HTML parsing